

DIGITAL PORTABLE CRANE SCALE



TENSION

CASE INCLUDED

(for capacities from 3000 to 10000 kg)

- CAPACITY UP TO 30 TONS
- ACCURACY CLASS (% OF FULL SCALE) $\pm 0.01\%$
- IP64 PROTECTION RATING



NOMINAL LOAD (FS)

kg	kN	ACCURACY CLASS (% OF FULL SCALE)	DIVISION (kg)	CRANE SCALES NET WEIGHT (kg)	HOOK NET WEIGHT (kg)	UK CA
3 000	30	0.7	e = 1	6.4	3	•
5 000	50	0.7	e = 2	8.8	5.5	•
10 000	100	0.7	e = 5	24	5.9	•
20 000	200	3.7	e = 10	45	–	•
30 000	300	4.8	e = 10	62	–	•



TECHNICAL DATA

DESCRIPTION AND MAIN FUNCTIONS

Description	- Crane scale in high resistance aluminum alloy (DTEZ3/5) and steel (DTEZ10/20/30) complete with upper and lower shackles. 5-digit backlit LCD display (25 mm height). 10 signalling symbols. - IP64 protection rating. 3 batteries 1.5 V AA type included. - Operating time: 50 hours. - Aluminum case included (DTEZ3/5/10). - Hook for for 3 to 10 tons capacity (option on request). - Remote control with range up to 15 m line of sight (option on request).
Main functions	- Weight totalizing. - Semi-automatic tare (net/gross weight). - Weight zero setting. - Tare weight zero setting. - Displaying of the maximum weight value reached (peak). - Units of measure setting: kg - t - N - kN - lb. - Energy saving mode. - Auto power-off. - Access to calibration functions via remote control (option on request). - Printing of weighing data via remote control (option on request).

TECHNICAL FEATURES


Working load limit without releasing the load (% of full scale)	300%
Safe overload (% of full scale)	200%
Working temperature	-10°C +40°C

COMPLIANCE AND CERTIFICATION



Protection Rating	IP64
Compliance	CE, RoHS, REACH
Calibration	Factory-calibrated, ISO 17025 calibration available on request
HS-CODE	9031.80.80
Certifications	 Equivalent of the CE marking for the United Kingdom
Certifications (on request)	 Accredia traceable calibration report




DIMENSIONS (mm)



mm	DTEZ3	DTEZ5
A	260	285
B	123	123
C	39	55
D	103	120
H1	365	405
H2	555	635
E	55	65
F	Ø51	Ø58
G	30	34
L	37	53



HOOK OPTION



mm	DTEZ10	DTEZ20	DTEZ30
A	320	375	420
B	120	128	138
C	55	72	84
D	183	230	265
H1	535	660	740
H2	840	-	-
E	95	-	-
F	Ø92	Ø127	Ø146
G	-	-	-
L	53	70	82



OPTIONS ON REQUEST

	DESCRIPTION	CODE
	Remote control with display, range up to 15 m line of sight.	TELEDTEZ
	Remote control with display and printer, range up to 15 m line of sight.	TELEDTEZPRINT
	Hook for capacities up to 3000 kg Hook for capacities up to 5000 kg Hook for capacities up to 10000 kg	

