

COMPRESSION COLUMN LOAD CELL



- LOW PROFILE
- COMBINED ERROR $\leq \pm 0.028 \%$
- IP67 PROTECTION RATING
- 17-4PH STAINLESS STEEL | 1.4542



NOMINAL LOAD (FS)

kN	t	Net weight (kg)	Combined error	ISO 17025	High Temperature -40...250°C	Rated Output (mV/V)
50	5	~2	$\leq \pm 0.028 \%$	(optional)	(optional)	2.0 $\pm 0,5\%$
100	10	~2	$\leq \pm 0.028 \%$	(optional)	(optional)	2.0 $\pm 0,5\%$
200	20	~2	$\leq \pm 0.028 \%$	(optional)	(optional)	2.0 $\pm 0,5\%$
500	50	~2	$\leq \pm 0.028 \%$	(optional)	(optional)	2.0 $\pm 0,5\%$
1 000	100	~5	$\leq \pm 0.028 \%$	(optional)	(optional)	2.0 $\pm 0,5\%$
2 000	200	~12	$\leq \pm 0.028 \%$	(optional)	(optional)	2.0 $\pm 0,5\%$
3 000	300	~21	$\leq \pm 0.028 \%$	(optional)	(optional)	2.0 $\pm 0,5\%$



TECHNICAL DATA

PRECISION

Rated Output (C_n)	2.0 mV/V $\pm 0,5$ % at FS
Zero Balance	$< \pm 1.0$ %
Combined error	$\leq \pm 0.028$ %FS
Non-linearity	$\leq \pm 0.02$ %FS
Hysteresis	$\leq \pm 0.02$ %FS
Repeatability	$\leq \pm 0.02$ %FS
Creep	$\leq \pm 0.02$ %FS (at 30 min FS)
Temperature coefficient of zero	0.005 %FS/°C
Temperature coefficient of sensitivity	0.005 %FS/°C
Compensated temperature range	-10...+60 °C
Operating temperature range	-30...+70 °C
Reference Temperature	23 °C

MECHANICAL PROPERTIES

Material	17-4 PH STAINLESS STEEL 1.4542
Deflection at FN	~ 0.4 mm

ELECTRICAL PROPERTIES

Bridge configuration	Full Wheatstone bridge, 6-wire
Input resistance	$760 \pm 20 \Omega$
Output resistance	$700 \pm 20 \Omega$
Insulation resistance	$\geq 5\,000\text{ M}\Omega$ at 100 V
Recommended excitation voltage	5 - 15 V
Cable diameter	5.4 mm
Cable length	6 000 mm


MECHANICAL LIMITS

Service load	120 %FS	Load without any permanent deformation or change in calibration.
Safe overload	150 %FS	The highest static load that may be applied once or briefly without mechanical damage.
Breaking load	> 300 %FS	Load at which permanent deformation or mechanical failure (fracture) occurs.
Max. transverse load (side)	50 %FS	Maximum lateral or shear load that can be applied (e.g. due to misalignment or friction).
Max. permissible dynamic load	70 %FS	For cyclic or oscillating loads, the amplitude should not exceed this load to prevent fatigue failure.

COMPLIANCE AND CERTIFICATION

Protection Rating	IP67 (IEC 60529)
Compliance	CE, RoHS, REACH
Calibration	Factory-calibrated, ISO 17025 calibration available on request
HS-CODE	9031.80.80

DIMENSIONS



ELECTRICAL CONNECTION

