


MOUNTING KIT FOR SHEAR BEAM LOAD CELLS



- GALVANIZED STEEL
- UP TO 2 000 KG APPLICATION RANGE
- ADJUSTABLE HEIGHT



Galvanized Steel



Stainless Steel
AISI 304 - 1.4301

MAX STATIC LOAD

kg	N	Net weight (kg)	For load cells
2 000	20 000	2.7	LBLF - LBLL - LBLA - LBLK - LBLJ

Load cell not included




DESCRIPTION AND MOUNTING


DESCRIPTION

- AISI 304 stainless steel upper plate.
- Lower plate and block in galvanized steel (TFPS2000) or in stainless steel (TFPS2000INOX).
- Constraint against lateral forces and anti-tilt by means of ball-and-socket joint with nut in galvanized C40 steel (TFPS2000) or in stainless steel (TFPS2000INOX).
- Compensation for any misalignments of the support plates of the structure.
- Adjustable height.
- Locking screw to avoid damage during transport and installation.

TFPS2000



TFPS2000INOX




2 000 kg
20 kN

MOUNTING NOTES

- During the transport and installation the lock (*) must touch under the load cell. After installation, move the lock away from the load cell.
- Interconnect the plates to the earthing.
- In case of structure with four-point support, if one-point does not touch the upper part of the mounting kit, you must proceed to insert a shim before fixing the bolts.
- For the load cell fixing screws (·), provide a tightening torque of 79 Nm.

EM
(M12 x 1.75) **EM-INOX**
(M12 x 1.75)



Tightening
torque:
79 Nm



DIMENSIONS (mm)

