


TENSION AND COMPRESSION LOAD CELL

TENSION & COMPRESSION



- LOW PROFILE
- COMBINED ERROR $\leq \pm 0.22 \%$
- IP67 PROTECTION RATING
- 17-4PH STAINLESS STEEL | 1.4542



NOMINAL LOAD (FS)

N	kg (optional)	Net weight (kg)	Combined error	ISO 17025	High Temperature -40...250°C	Rated Output (mV/V)
100	10	0.6	$\leq \pm 0.22 \%$	(optional)	(optional)	1.5 $\pm 10\%$
200	20	0.6	$\leq \pm 0.22 \%$	(optional)	(optional)	1.5 $\pm 10\%$
500	50	0.6	$\leq \pm 0.22 \%$	(optional)	(optional)	1.5 $\pm 10\%$
1 000	100	0.6	$\leq \pm 0.22 \%$	(optional)	(optional)	1.5 $\pm 10\%$
2 000	200	0.6	$\leq \pm 0.22 \%$	(optional)	(optional)	1.5 $\pm 10\%$
5 000	500	0.6	$\leq \pm 0.22 \%$	(optional)	(optional)	1.5 $\pm 10\%$



TECHNICAL DATA

PRECISION

Rated Output (C _n)	1.5 mV/V ±10 % at FS
Zero Balance	< ±0.03 %
Combined error	≤ ±0.22 %FS
Non-linearity	≤ ±0.2 %FS
Hysteresis	≤ ±0.1 %FS
Repeatability	≤ ±0.1 %FS
Creep	≤ ±0.05 %FS (at 30 min FS)
Temperature coefficient of zero	-0.005 %FS/°C
Temperature coefficient of sensitivity	0.005 %FS/°C
Compensated temperature range	-10...+60 °C
Operating temperature range	-20...+80 °C
Reference Temperature	23 °C

MECHANICAL PROPERTIES

Material	17-4PH STAINLESS STEEL 1.4542
Deflection at FN	~ 0.5 mm

ELECTRICAL PROPERTIES

Bridge configuration	Full Wheatstone bridge, 4-wire
Input resistance	760 - 800 Ω
Output resistance	690 - 710 Ω
Insulation resistance	≥ 5 000 MΩ at 100 V
Recommended excitation voltage	5- 15 V
Cable diameter	4 mm
Cable length	4 000 mm


MECHANICAL LIMITS

Service load	120 %FS	Load without any permanent deformation or change in calibration.
Safe overload	150 %FS	The highest static load that may be applied once or briefly without mechanical damage.
Breaking load	> 200 %FS	Load at which permanent deformation or mechanical failure (fracture) occurs.
Max. transverse load (side)	50 %FS	Maximum lateral or shear load that can be applied (e.g. due to misalignment or friction).
Max. permissible dynamic load	70 %FS	For cyclic or oscillating loads, the amplitude should not exceed this load to prevent fatigue failure.


COMPLIANCE AND CERTIFICATION

Protection Rating	IP67 (IEC 60529)
Compliance	CE, RoHS, REACH
Calibration	Factory-calibrated, ISO 17025 calibration available on request
HS-CODE	9031.80.80

DIMENSIONS

				
Cap (kN)	A	B	C	M
1, 2, 5, 10, 20	71	19	18	M12
50	86	25	25	M16

ELECTRICAL CONNECTION

	+ EXCITATION	RED
	- EXCITATION	BLACK
	+ SIGNAL	GREEN
	- SIGNAL	WHITE
	SHIELD	

